

SAFETY DATA SHEET

PRODUCT NAME

1M-Lithiumu Chloride Solution [Ethanol solvent] (Internal solution for electrode) Data of issue 30/1/2012 Date of revision 2/4/2024 (Confirmation)

1. Identification of the substance or mixture and the supplier

Product name	1M-Lithiumu Chloride Solution [Ethanol solvent] (Internal solution for electrode)		
SDS No.	GHS-0052E		
Name of supplier	Kyoto Electronics Manufacturing Co., Ltd.		
Address	68 Ninodan-cho, Shinden, Kisshoin, Minami-ku, Kyoto, Japan		
Division	Quality Assurance Department		
Phone	+81-75-691-4121		
Fax	+81-75-691-4127		
Recommended uses and restrictions on use			
Recommended use	For analysis		
Restrictions on use	When using for purposes other than those recommended, consult a specialist.		

2. Hazard identification

GH	S classification	
Ph	ysical hazards	
	Flammable liquids	Category 2
He	ealth hazards	
	Serious eye damage / Eye irritation	Category 2A
	Carcinogenicity	Category 1A
	Reproductive toxicity	Category 1A
	Specific target organ toxicity (single exposure)	Category 3(respiratory tract irritation)
		Category 3(anesthetic action)
	Specific target organ toxicity (repeated exposure	Category 2(central nervous system)
		Category 1(liver)

GHS label elements





Hazard statements :	H224 Highly flammable liquids and vapors.
	H319 Strong eye irritation.
	H335 May cause respiratory irritation.
	H336 May cause drowsiness or dizziness.
	H350 May cause cancer.
	H360 May cause adverse effects on fertility or the
	unborn child.
	H372 Liver damage from prolonged or repeated
	exposure.
	H373 May cause damage to Central Nervous System
	through prolonged or repeated exposure.
Precautionary statement	
Prevention	P201 Obtain special instructions before use.
	P210 Keep away from heat / sparks / open flames / hot
	ignition sources. No smoking. P233: Keep container
	tightly closed.
	P233: Keep container tightly closed.
	P260 Do not breathe dust / fume / gas / mist / vapors /
	spray.
	P280 Wear protective gloves / protective clothing/eye
	protection / face protection.
Response	P308+P313 IF exposed or concerned: Get medical
	advice/attention.
	P370+P378 In case of fire: Use appropriate
	extinguishing media to extinguish.
Other hazards which do not result in classification	None known.

3. Composition/Information on ingredients

mixture

```
Components
```

No.	Chemical name	CAS No.	Concentration	ENCS / ISHL
			(% w/w)	number
1	Ethanol	64-17-5	94.9%	2-202
2	Lithium Chloride	7447-41-8	5.1%	1-231

4. First-aid measures



General advice	Do not leave the victim unattended.		
If inhaled	Remove victim to fresh air.		
	Call a doctor/physician if you feel unwell.		
In case of skin contact	Wash off with soap and plenty of water.		
	If symptoms persist, contact a physician.		
In case of eye contact	Rinse cautiously with water for several minutes.		
	Remove contact lenses, if present and easy to do. Continue rinsing.		
	Contact a physician immediately.		
If swallowed	Rinse mouth with water.		
	Do NOT induce vomiting.		
	Never give anything by mouth if unconscious.		
	If large quantities of this material are swallowed, call a physician immediately.		
Most important symptoms	No information		
and effects, both acute and			
delayed			
Notes to physician	Treat symptomatically.		

5. Fire-fighting measures

Suitable extinguishing media	Spray water, carbon dioxide (CO2), dry sand, fire retardant		
Unsuitable extinguishing media	Large bar water		
Specific hazards during fire	In case of fire, prevent water for firefighting from flowing into drains or		
fighting	waterways.		
Specific extinguishing methods	Collect contaminated firefighting wastewater. Do not discharge it into drainage		
	facilities.		
	Dispose of fire residues and contaminated wastewater in accordance with		
	applicable regulations.		
Special protective equipment for	Use personal protective equipment.		
fire-fighters			

6. Accidental release measures

Personal precautions,	Use personal protective equipment.	
protective equipment and	Remove all sources of ignition.	
emergency procedures		
Environmental precautions	Prevent further leakage or spillage if safe to do so.	
	If the product contaminates rivers and lakes or drains inform respective authorities.	
Methods and materials for	Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal	



containment and cleaning up binder, sawdust).

Keep in suitable, closed containers for disposal.

7. Handling and storage

Handling

Technical measures	Handle in an enclosed facility, local exhaust ventilation, or general
	ventilation facility. Provide adequate work area ventilation. Avoid
	breathing vapors (dust).
Precautions for safe handling	Prohibit the use of high temperature objects, sparks and fire in the
	vicinity. Do not eat, drink or smoke when using this product. Do not
	inhale or swallow. Do not breathe dust. After handling Wash hands
	thoroughly.
	Take precautionary measures against static discharge.
Avoiding incompatibilities	No information
Storage	
Conditions for safe storage	Store in a well-ventilated place. Keep container tightly closed.
Container and packaging material for	Store in a closed container.
safe storage	

8. Exposure controls/Personal protection

1	1	1		
Components	CAS-No.	Value type	Control parameters /	Basis
		(Form of	Reference concentration /	
		exposure)	Permissible concentration	
Ethanol	64-17-5	STEL	1000 ppm	ACGIH

Threshold limit value and permissible exposure limits for each component in the work environment

Personal protective equipment

Respiratory protection	Suitable respiratory equipment
Hand protection material	Protective gloves
Eye protection	Safety glasses
Skin and body protection	Protective suit

9. Physical and chemical properties

Physical state	Liquid
Color	Colorless and transparent
Odor	Peculiar odor



Melting point / Freezing point	No data available
Initial boiling point and boiling range	No data available
Flammability (liquids)	No data available
Lower explosion limit and upper explosion limit / flamm	ability limit
Upper explosion limit / Upper flammability limit	No data available
Lower explosion limit / Lower flammability limit	No data available
Flash point	No data available
Decomposition temperature	No data available
рН	No data available
Autoignition temperature	No data available
Self-Accelerating decomposition temperature	No data available
(SADT)	
Viscosity	
Viscosity, kinematic	No data available
Solubility(ies)	
Water solubility	Easily soluble
Partition coefficient: n-octanol/water	No data available
Vapor pressure	No data available
Density and / or relative density Relative density	No data available
Relative vapor density	No data available
Particle characteristics Particle size	No data available

10. Stability and reactivity

Reactivity	No data available
Chemical stability	Stable under normal conditions.
Possibility of hazardous reactions	No data available
Conditions to avoid	No product data available. However, as the main component Ethanol,
	avoid contact with heat, flame, sparks, high temperature and direct
	sunlight, static electricity, and sparks.
Incompatible materials	No product data available. However, avoid the contact of Ethanol, the
	main ingredient, with strong oxidants.
Hazardous decomposition products	No data available

11. Toxicological information

Acute toxicity

Ethanol



LD50(Oral)	Rat	6200mg/kg	
LD50(Dermal)	Rabbit	20000mg/kg	
Lithium Chloride			
LD50(Oral)	Rat	526-840mg/kg	[1]
LD50(Dermal)	Rat	1488mg/kg	[1]
Skin Corrosion / Irritation			
Lithium Chloride	Category 2		
Serious eye damage / Eye irritation			
Ethanol	Category 2	В	
Lithium Chloride	Category 2	A	
Carcinogenic			
Ethanol	Category 1	A	
Specific target organ toxicity(single e	xposure)		
Ethanol	Category 3	(respiratory tract irritation, anesthetic action)	
Lithium Chloride	Category 2	(nervous system)	
Specific target organ toxicity(repeate	d exposure)		
Ethanol	Category 2	(central nervous system)	
Lithium Chloride	Category 2	(nervous system, kidney)	
Acute toxicity			
Ethanol			
Acute oral toxicity	LD50 (Rat) 15,0	10 mg/kg	
Acute inhalation toxicity	LC50 (Rat) 124.	7 mg/L , Exposure time 4 h , test environment vapor	
Acute dermal toxicity	LDLo (Rabbit) 20),000 mg/kg	
Lithium Chloride			
Acute oral toxicity	LD50 (Rat) 526	· 840 mg/kg	
Acute oral toxicity Acute dermal toxicity	LD50 (Rat) 526 - LD50 (Rabbit) 1,	- 840 mg/kg 488 mg/kg	
Acute oral toxicity Acute dermal toxicity Skin corrosion/irritation	LD50 (Rat) 526 LD50 (Rabbit) 1, May cause skin irr	· 840 mg/kg 488 mg/kg itation and/or dermatitis.	
Acute oral toxicity Acute dermal toxicity Skin corrosion/irritation Lithium Chloride	LD50 (Rat) 526 - LD50 (Rabbit) 1, May cause skin irr Skin irritation	· 840 mg/kg 488 mg/kg itation and/or dermatitis.	
Acute oral toxicity Acute dermal toxicity Skin corrosion/irritation Lithium Chloride Serious eye damage/eye irritation	LD50 (Rat) 526 LD50 (Rabbit) 1, May cause skin irr Skin irritation Cause eye damag	- 840 mg/kg 488 mg/kg itation and/or dermatitis. e	
Acute oral toxicity Acute dermal toxicity Skin corrosion/irritation Lithium Chloride Serious eye damage/eye irritation Ethanol	LD50 (Rat) 526 LD50 (Rabbit) 1, May cause skin irr Skin irritation Cause eye damag Cause eye damag	- 840 mg/kg 488 mg/kg itation and/or dermatitis. e e	
Acute oral toxicity Acute dermal toxicity Skin corrosion/irritation Lithium Chloride Serious eye damage/eye irritation Ethanol Lithium Chloride	LD50 (Rat) 526 - LD50 (Rabbit) 1, May cause skin irr Skin irritation Cause eye damag Cause eye damag Eye irritation.	- 840 mg/kg 488 mg/kg itation and/or dermatitis. e e	
Acute oral toxicity Acute dermal toxicity Skin corrosion/irritation Lithium Chloride Serious eye damage/eye irritation Ethanol Lithium Chloride Respiratory or skin sensitization	LD50 (Rat) 526 - LD50 (Rabbit) 1, May cause skin irr Skin irritation Cause eye damag Cause eye damag Eye irritation.	- 840 mg/kg 488 mg/kg itation and/or dermatitis. e e	
Acute oral toxicity Acute dermal toxicity Skin corrosion/irritation Lithium Chloride Serious eye damage/eye irritation Ethanol Lithium Chloride Respiratory or skin sensitization Skin sensitization	LD50 (Rat) 526 - LD50 (Rabbit) 1, May cause skin irr Skin irritation Cause eye damag Cause eye damag Eye irritation.	- 840 mg/kg 488 mg/kg itation and/or dermatitis. e e e	
Acute oral toxicity Acute dermal toxicity Skin corrosion/irritation Lithium Chloride Serious eye damage/eye irritation Ethanol Lithium Chloride Respiratory or skin sensitization Skin sensitization	LD50 (Rat) 526 LD50 (Rabbit) 1, May cause skin irr Skin irritation Cause eye damag Cause eye damag Eye irritation. Not classified base Not classified base	- 840 mg/kg 488 mg/kg itation and/or dermatitis. e e e e ed on available information. ed on available information.	
Acute oral toxicity Acute dermal toxicity Skin corrosion/irritation Lithium Chloride Serious eye damage/eye irritation Ethanol Lithium Chloride Respiratory or skin sensitization Skin sensitization Respiratory sensitization Germ cell mutagenicity	LD50 (Rat) 526 - LD50 (Rabbit) 1, May cause skin irr Skin irritation Cause eye damag Cause eye damag Eye irritation. Not classified base Not classified base	- 840 mg/kg 488 mg/kg itation and/or dermatitis. e e e e ed on available information. ed on available information.	
Acute oral toxicity Acute dermal toxicity Skin corrosion/irritation Lithium Chloride Serious eye damage/eye irritation Ethanol Lithium Chloride Respiratory or skin sensitization Skin sensitization Respiratory sensitization Germ cell mutagenicity Carcinogenicity	LD50 (Rat) 526 - LD50 (Rabbit) 1, May cause skin irr Skin irritation Cause eye damag Cause eye damag Eye irritation. Not classified base Not classified base Not classified base Suspected of caus	- 840 mg/kg 488 mg/kg itation and/or dermatitis. e e e e ed on available information. ed on available information. ed on available information.	

STOT-single exposure	May cause respiratory irritation.
	May cause drowsiness or dizziness.
	This substance or mixture is classified as a specific target organ toxicant,
	single exposure, category 3 with airway irritation.
	This substance or mixture is classified as a specific target organ toxicant,
	single exposure, category 3 with anesthetic effects.
Ethanol	This substance or mixture is classified as a specific target organ toxicant,
	single exposure, category 3 with airway irritation.
	This substance or mixture is classified as a specific target organ toxicant,
	single exposure, category 3 with anesthetic effects.
STOT-repeated exposure	May cause damage to organs (central nervous system) due to long-term or
	repeated exposure.
	May cause damage to organs (liver) due to long-term or repeated exposure.
Aspiration toxicity	Not classified based on available information.
Remarks	Possible symptoms of overexposure include headache, dizziness, fatigue,
	nausea, and vomiting.
	Concentrations significantly higher than the TLV may cause coma effects.
	Solvents may debride the skin.

12. Ecological information

Ecotoxicity	
Ethanol	
Toxicity to fish	LC50 (Oncorhynchus mykiss (rainbow trout)) 13,000 mg/L, Exposure time 96 h
Toxicity to daphnia and other	EC50 (Daphnia magna (Water flea)) 12,340 mg/L, Exposure time 48 h
aquatic invertebrates	
Toxicity to algae/aquatic	EC50 (Lemna minor (duckweed)) 3,690 mg/L, End point Growth inhibition,
plants	Exposure time 7 Days
	NOEC (Lemna gibba (gibbous duckweed)) 280 mg/L, End point Growth
	inhibition,
	Exposure time 7 Days
Toxicity to daphnia and other	NOEC (Ceriodaphnia dubia (Water flea)) 9.6 mg/L, End point Reproductive
aquatic invertebrates (Chronic	inhibition, Exposure time 10 Days
toxicity)	
Lithium Chloride	
Toxicity to fish	EC50 (Ptychocheilus lucius) 17 mg/L, Exposure time 96 h
Persistence and degradability	
Ethanol	Biochemical oxygen demand rapidly biodegradable, Biodegradation 89 %,



Bioaccumulative potential		
Ethanol	Partition coefficient: n-octanol/water	log Pow = - 0.31
Mobility in soil	No data available	
Hazardous to the ozone layer	No data available	
Other adverse effects	No data available	

13. Disposal considerations

Waste from	Can be incinerated, when in compliance with local regulations.
residues	Send to a licensed waste management company.
Contaminated	Empty remaining contents.
packaging	Empty containers should be taken to an approved waste handling site for recycling or disposal.
	Dispose of contents/ container to an approved waste disposal plant.

14. Transport information

International Regulations	
IATA-DGR	
UN / ID No.	UN1170
Proper shipping name	ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION)
Class	3
Packing group	Π
Labels	G
IMDG-Code	
UN No.	UN1170
Proper shipping name	ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION)
Class	3
Packing group	Π
Marine pollutant	no
Transport in bulk according to Annex II of M	ARPOL 73/78 and the IBC Code
	Not applicable for product as supplied.
Domestic regulation	Please refer to the law and local regulations, etc. in each country
Special precautions for user	The transport classification(s) provided herein are for informational
	purposes only, and solely based upon the properties of the unpackaged
	material as it is described within this Safety Data Sheet. Transportation
	classifications may vary by mode of transportation, package sizes, and
	variations in regional or country regulations.



15. Regulatory information

16. Other information

Full text of other abbreviations ACGIH ACGIH / STEL

USA. ACGIH Threshold Limit Values (TLV) Short-term exposure limit

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM -American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS -Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP -Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR -No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS -Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS -Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing,



storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.