

SAFETY DATA SHEET

PRODUCT NAME Viscosity Liquid 200

Data of issue

5/19/2014

Date of revision/ Last confirmation

3/4/2025

1. Identification of the substance or mixture and the supplier

Product name Viscosity Liquid 200

SDS No. GHS-0050E

Name of supplier Kyoto Electronics Manufacturing Co., Ltd.

Address 68 Ninodan-cho, Shinden, Kisshoin, Minami-ku, Kyoto, Japan

Division Quality Assurance Department

Phone +81-75-691-4121
Fax +81-75-691-4127
Emergency phone +81-75-691-4125

Recommended uses and restrictions on use

Recommended use For analysis

Restrictions on use When using for purposes other than those recommended, consult a specialist.

2. Hazard identification

GHS classification Not a hazardous substance or mixture according to the

Globally Harmonized System (GHS).

GHS label elements Not a hazardous substance or mixture according to the

Globally Harmonized System (GHS).

Other hazards which do not result in classification

Important symptoms and outlines of the emergency None known.

assumed

3. Composition/Information on ingredients

substance / mixture mixture

Components

No.	Chemical name	CAS No.	Concentration	ENCS / ISHL
			(% w/w)	number
1	Base oil (Cannot be disclosed due to trade secret.)	8042-47-5	100	_

If product contained highly refined mineral oil, it contains <3 % DMSO-extract, according to IP346.



4. First-aid measures

General advice Do not leave the victim unattended.

If inhaled Remove victim to fresh air.

Cover the body with a blanket etc. to keep warm and rest, and seek medical attention

immediately.

In case of skin contact Wash the affected area with soap and water.

In case of eye contact Flush eyes with clean water for at least 15 minutes and then seek medical attention.

If swallowed Do not induce vomiting, and seek medical attention immediately.

If the inside of the mouth is contaminated, rinse thoroughly with water.

and effects, both acute and If it comes into contact with eyes, it may cause irritation.

delayed If it comes into contact with skin, it may cause irritation.

Inhaling mist may cause nausea.

5. Fire-fighting measures

Suitable extinguishing media Mist-type reinforced liquid, foam, powder or carbon dioxide extinguishing agents

are effective.

For early-stage fires, use powder or carbon dioxide extinguishers.

For large-scale fires, use extinguishing agents such as foam that are effective

at cutting off the oxygen/air supply to the fire.

Unsuitable extinguishing media High volume water jet

Specific hazards during fire No data available.

fighting

Specific extinguishing methods
Cut off any sources that might further fuel the fire.

Spray water on the surrounding area (covering tools and equipment if

necessary and safe to do so) to cool everything down.

Prevent anyone not immediately responsible for the work or the emergency

response from entering the location of the fire.

Special protective equipment for

fire-fighters

Extinguishing work should be done from the upwind/windward position (stand in

a place opposite to the direction of toxic fumes and smoke) while wearing PPE.

6. Accidental release measures

Personal precautions, Prepare fire extinguishing equipment.



protective equipment and Wear fire protection gear when working.

emergency procedures

Environmental precautions Be careful not to discharge into rivers, sewers, etc.

When using chemicals at sea, they must comply with the technical standards set out in ordinances of the Ministry of Land, Infrastructure, Transport and Tourism and the

Ministry of the Environment.

Methods and materials for

Immediately remove all nearby sources of ignition.

completely with rags, etc.

If the amount is large, string up ropes around the area below the spill to prevent people from entering. Stop the flow of the leaked liquid with sand, etc., guide it to a

safe place, and collect as much as possible in empty containers, etc.

If at sea, deploy oil fences to prevent the liquid from spreading, and soak up the liquid with absorbent mats, etc. (however, this does not apply if the density is 1 or higher). If chemicals are used, they must comply with the technical standards set out in ordinances of the Ministry of Land, Infrastructure, Transport and Tourism and the

Ministry of the Environment.

7. Handling and storage

Handling

Advice on protection against fire and Steam generated from petroleum products is heavier than air and tends

explosion to stagnate, so care must be taken with ventilation and fire.

Advice on safe handling Handle at room temperature, taking care to avoid contamination with

moisture or foreign matter.

Avoidance of contact Halogens, strong acids, alkalis, oxidizing substances

Hygiene measures When using do not eat or drink.

When using do not smoke.

Wash hands before breaks and at the end of workday.

Storage

Conditions for safe storage Store in a well-ventilated place away from direct sunlight.

After use, seal tightly to prevent contamination by dust, moisture, etc.

Store in a locked container.

Avoid heat, sparks, flames, and static electricity buildup.

Further information on storage Do not pressurize empty containers as they may burst.

stability Do not weld, heat, drill or cut containers as residues may ignite with

explosion.



8. Exposure controls/Personal protection

Threshold limit value and permissible exposure limits for each component in the work environment

Components	CAS-No.	Value type	Control parameters /	Basis
		(Form of	Reference concentration /	
		exposure)	Permissible concentration	
(as oil mist, mineral)			3 mg/m ³	JSOH
		TWA	5 mg/m ³	ACGIH

Personal protective equipment

Respiratory protection Suitable respiratory equipment

Hand protection material Protective gloves

Eye protection Safety glasses

Skin and body protection Protective suit

9. Physical and chemical properties

Physical state Liquid.

Color Transparent
Odor Slight odor

Melting point / Freezing point No data available
Initial boiling point and boiling range No data available
Flammability (liquids) No data available

Lower explosion limit and upper explosion limit / flammability limit

Upper explosion limit / Upper flammability limit

1 vol%

Lower explosion limit / Lower flammability limit

7 vol%

Flash point

220 ℃

Decomposition temperature

PH

No data available

Self-Accelerating decomposition temperature

No data available

(SADT) Viscosity

Viscosity, kinematic 201 mm²/s (20 ℃)

Solubility(ies)

Water solubility Insoluble

Solubility in other solvents

Partition coefficient: n-octanol/water

Vapor pressure

No data available

No data available



Density and / or relative density Relative density 0.86 g/cm³ (15 ℃)

Relative vapor density No data available

Particle characteristics Particle size No data available

10. Stability and reactivity

Reactivity Avoid contact with strong oxidizing agents.

Chemical stability Stable under normal conditions.

Possibility of hazardous reactions

No data available

Conditions to avoid Avoid contact with halogens, strong acids, alkalis, and oxidizing

substances.

Incompatible materials No data available

11. Toxicological information

Acute toxicity

Acute oral toxicity LD50(Rat) >5,000 mg/kg

Acute dermal toxicity LD50(Rabbit) >5,000 mg/kg

Acute inhalation toxicity LC50(Rat) > 5 mg/L

Skin corrosion/irritation Not expected to be irritating to the skin. However, continued or repeated contact

may cause mild skin irritation.

Serious eye damage/eye irritation

Not expected to cause eye irritation, however may cause mild eye irritation.

Respiratory or skin sensitization

Skin sensitization Not data available
Respiratory sensitization Not data available
Germ cell mutagenicity Not data available

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT-single exposure

Not classified based on available information.

STOT-repeated exposure

Not classified based on available information.

Aspiration toxicity Carbohydrates with a kinematic viscosity of 20.5 mm²/s or less at 40°C are

classified as Category 1.

Remarks No data available

12. Ecological information

Ecotoxicity LC/LL/EL/IL50 >100 mg/L

Persistence and This material is not expected to be immediately biodegradable, but is expected to



degradability eventually biodegrade.

Bioaccumulation Although not expected to bioaccumulate, it may contain components that may

bioaccumulate.

Mobility in soil The log Koc of similar base oils is estimated to be 3 or higher, and it is unlikely that oil

leaking on the surface would flow into groundwater due to adsorption by the soil.

Hazardous to the ozone

Not applicable

layeı

Other adverse effects Cause fouling of aquatic organisms.

13. Disposal considerations

Waste from Businesses must dispose of industrial waste themselves, or entrust it to an industrial waste

residues disposal company licensed by the prefectural governor, or to a local government if the local

government is handling such disposal. Disposal must follow the relevant laws and regulations

and the standards of the local government.

Dumping prohibited

When disposing of waste in a landfill, it must be incinerated in advance using incineration

equipment, and it must be confirmed that the resulting cinders are below the standards set out

in the Enforcement Order of the Waste Disposal and Public Cleansing Law.

When incinerating waste, it must be done in a safe place, in a manner that will not cause harm

or damage to others due to incineration or explosion, and a guard must be present.

Contaminated Clean and recycle the container or dispose of it appropriately in accordance with the relevant

laws and regulations and local government standards. When disposing of the empty container,

remove all contents.

14. Transport information

International Regulations

packaging

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation Please refer to the law and local regulations, etc. in each country

Special precautions for user Not applicable

15. Regulatory information

16. Other information



Citations/References

NITE-Gmiccs (National Institute of Technology and Evaluation)

NITE-CHRIP (National Institute of Technology and Evaluation)

Workplace Safety Site (Ministry of Health, Labor and Welfare)

SDS from various upstream manufacturers

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.